

## Slim-Edg™


### LANDSCAPE EDGING

#### 5 INCH LOW-PROFILE EDGING WITH A 2 INCH STRAIGHT TOP AND 4 GROOVE WALL ANCHOR



Created in the likeness of Edg-King™, this similarly thick cousin is designed with a double v-lip anchoring wall; therefore, preventing frost heave better than any other v-lip style. Since Black Edg-Knight™ achieves the same great results as its predecessor, choosing between the two basically comes down to personal taste.

Black Edg-Knight™ is made with high grade, recycled polyethylene, with no fillers or blown in material. It is made to last!



Available in 20 and 10 ft. lengths



	SPECIFICATIONS
Packaging:	20 foot - 5 pieces per flat bundle 10 foot - 5 pieces per flat bundle
Material:	Pure medium density polyethylene and 4% carbon black concentrate. Melt factor under 2
Average Wall Thickness:	Top 2 inches: .20 - .30 inches Wall: .09 - .105 inches
Dimensions Per Piece:	Length: 20 ft. Height: 5 in.
Features:	2 in. straight top 4 groove horizontal wall anchor
Can be Formed with Heat:	Yes - heat gun or propane torch ( <i>No Contact</i> )
Connection Type:	Connecting Cap ( <i>Sold Separately</i> )
Staking:	Through edging wall at 45° angle using nail or Oly-Ola's 9.25 inch stake ( <i>Sold Separately</i> )
Approx. Weight:	20 ft. piece: 6.8 lbs.      10 ft. piece: 3 lbs. 20 ft. bundle: 34 lbs.      10 ft. bundle: 15 lbs.



## Installation Guidelines & Tips

### BASICS

Dig a trench 5 inches deep along the lawn or bed edge. Place the edging in the trench and anchor it with stakes as indicated above. Use the provided connecting clip when joining two lengths of edging together and be sure to use the overlap method pictured below.

### STAKING

Pound a stake through the edging wall every 4 feet at a 45 degree angle. The stake should be installed at about the midway point of the wall. Pound the stake through the edging but **be sure to leave at least 2 inches undriven** to allow for resistance on both sides of the wall. Use extra stakes when securing joints and curves. Do not make the mistake of using too few stakes, especially when the ground is exposed to cold temperatures.

### JOINING


Use the overlap method detailed below. A polyethylene approved adhesive can be used for a permanent hold. We recommend Bondit B-45TH by Reltek.

### CONNECTOR: CONNECTING CAP



For connecting pieces together, connecting caps are provided that can be fixed in place using poly approved adhesive or screws.


### OVERLAP METHOD (FOR JOINING LENGTHS): Guard Against Gapping & Frost Heave



1. Cut off a 4 inch section of the top of one of the edging pieces, just below the bottom bead, with a metal snip, utility knife or saw.



2. Use the connecting cap that comes with the edging to join the two sections while overlapping the two pieces of edging.



3. Drive 1 or 2 steel anchoring stakes through both sections at a 45 degree angle toward the turf or outside portion of the bed.



Discover  
**THE OLY-OLA**  
**EDGE**